

Roulements à une rangée de rouleaux coniques

φ d (mm)	Référence	Dimensions (mm)							Masse (kg)
		D	B	T	C	a	r _{min}	r _{lemin}	
110	13021A	160	43	43.00	34.0	11.7	2.5	2.0	3.050
	33121A	175	56	56.00	44.0	12.1	2.5	2.0	5.430
	30221A	190	36	39.00	30.0	0.8	3.0	2.5	4.260
	32221A	190	50	53.00	43.0	7.7	3.0	2.5	5.900
	30321A	225	49	53.50	41.0	9.7	4.0	3.0	9.400
	31321XA	225	53	58.00	36.0	-10.0	3.0	1.0	9.650
	32321A	225	77	81.50	63.0	25.8	4.0	3.0	14.600
	32922A	150	25	25.00	20.0	-1.4	1.5	1.5	1.290
	32022XA	170	38	38.00	29.0	1.5	2.5	2.0	3.060
	33022A	170	47	47.00	37.0	13.0	2.5	2.0	3.890
	33122A	180	56	56.00	43.0	10.8	2.5	2.0	5.550
	30222A	200	38	41.00	32.0	0.6	3.0	2.5	5.000
	32222A	200	53	56.00	46.0	8.5	3.0	2.5	6.900
	30322A	240	50	54.50	42.0	9.2	4.0	3.0	10.900
	31322XA	240	57	63.00	38.0	-9.0	3.0	1.0	11.960
120	32322A	240	80	84.50	65.0	26.6	4.0	3.0	16.600
	32924A	165	29	29.00	23.0	-0.3	1.5	1.5	2.210
	32024XA	180	38	38.00	29.0	-1.2	2.5	2.0	3.240
	33024A	180	48	48.00	38.0	11.8	2.5	2.0	4.200
	33124A	200	62	62.00	48.0	13.2	2.5	2.0	7.300
	30224A	215	40	43.50	34.0	-1.1	3.0	2.5	6.010
	32224A	215	58	61.50	50.0	8.4	3.0	2.5	8.570
	30324A	260	55	59.50	46.0	9.5	4.0	3.0	13.800
	31324XA	260	62	68.00	42.0	-10.0	4.0	3.0	15.500
	32324A	260	86	90.50	69.0	28.0	4.0	3.0	21.200
130	32926A	180	32	32.00	25.0	1.1	2.0	1.5	2.470
	32026XA	200	45	45.00	34.0	1.8	2.5	2.0	3.930
	33026A	200	55	55.00	43.0	11.7	2.5	2.0	6.440
	30226A	230	40	43.75	34.0	-2.8	4.0	3.0	6.790
	32226A	230	64	67.75	54.0	10.7	4.0	3.0	10.700
	30326A	280	58	63.75	49.0	10.9	5.0	4.0	17.200
	31326XA	280	66	77.00	44.0	-12.0	5.0	4.0	18.500
	32326A	280	93	98.75	78.0	30.4	5.0	4.0	26.200
140	32928A	190	32	32.00	25.0	-1.1	2.0	1.5	2.670
	32028XA	210	45	45.00	34.0	-0.8	2.5	2.0	5.230
	33028A	210	56	56.00	44.0	10.0	2.5	2.0	7.040

Roulements à une rangée de rouleaux coniques

φ d (mm)	Référence	Coefficients de calcul			Vit. limites (tr/mn)		Cap. de charge (daN)	
		e	Y1	Y0	Lubrific. grais. huile		Dyn. C	Stat. Co
110	33021A	0.28	2.12	1.17	2100	2900	24000	40000
	33121A	0.40	1.48	0.82	2000	2700	33500	53000
	30221A	0.42	1.43	0.79	1900	2600	27900	36500
	32221A	0.42	1.43	0.79	1900	2600	36000	51000
	30321A	0.35	1.74	0.96	1700	2300	43500	53500
	31321XA	0.83	0.72	0.40	1500	2000	40200	50000
	32321A	0.35	1.74	0.96	1700	2300	63500	87000
	32922A	0.36	1.69	0.93	2200	2900	11900	22200
	32022XA	0.43	1.39	0.77	2000	2700	23500	36000
	33022A	0.29	2.09	1.15	2000	2700	27300	46500
	33122A	0.42	1.43	0.79	1900	2600	34500	56000
	30222A	0.42	1.43	0.79	1800	2400	31000	41500
	32222A	0.42	1.43	0.79	1800	2400	39500	47000
	30322A	0.35	1.74	0.96	1600	2100	48000	59000
	31322XA	0.83	0.72	0.40	1400	1900	45700	58500
120	32322A	0.35	1.74	0.96	1600	2100	70000	96500
	32924A	0.35	1.72	0.95	1900	2600	14900	28100
	32024XA	0.46	1.31	0.72	1800	2500	24100	40000
	33024A	0.31	1.97	1.08	1800	2500	28100	49500
	33124A	0.40	1.51	0.83	1700	2300	43500	69000
	30224A	0.44	1.38	0.76	1600	2200	32500	44000
	32224A	0.44	1.38	0.76	1600	2200	43500	63500
	30324A	0.35	1.74	0.96	1400	2000	54000	67000
	31324XA	0.83	0.72	0.40	1300	1700	53900	69500
	32324A	0.35	1.74	0.96	1400	2000	81500	114000
130	32926A	0.34	1.77	0.97	1800	2400	19300	35000
	32026XA	0.44	1.38	0.77	1700	2300	31500	53000
	33026A	0.34	1.76	0.97	1700	2300	39000	72000
	30226A	0.44	1.38	0.76	1500	2100	34500	48000
	32226A	0.44	1.38	0.76	1500	2100	52500	78000
	30326A	0.35	1.74	0.96	1300	1800	64000	81000
	31326XA	0.83	0.72	0.40	1100	1600	60500	78000
	32326A	0.35	1.74	0.96	1300	1800	85500	132000
140	32928A	0.36	1.67	0.92	1700	2300	19900	37000
	32028XA	0.46	1.31	0.72	1600	2100	32000	54000
	33028A	0.36	1.67	0.92	1600	2100	34500	69500