

Butées à billes à simple effet à rondelles plates

φ d (mm)	Référence	Dimensions (mm)					Vitesses lim. (tr/mn)		Cap. de ch. (daN)		Masse (kg)
		D	H	Dimin	dmax	rsmn	Lubrification		Dyn.	Stat.	
							graisse	huile	C	Co	
90	51317	150	49	88	150	1.5	1900	1600	20000	49000	3.660
	51417X	180	72	88	177	2.1	840	1200	30500	75500	9.450
	51118	120	22	92	120	1.0	1900	2700	5950	19000	0.680
	51218	135	35	93	135	1.1	1400	2000	11600	32500	1.770
	51318	155	50	93	155	1.5	1100	1600	19800	49000	3.980
100	51418X	190	77	93	187	2.1	790	1100	32500	82500	11.200
	51120	135	25	102	135	1.0	1700	2400	8500	26800	0.990
	51220	150	38	103	150	1.1	1300	1800	14600	41000	2.360
	51320	170	55	103	170	1.5	990	1400	23600	51500	5.110
	51420X	210	85	103	205	3.0	710	1000	34500	89500	15.000
110	51122	145	25	112	145	1.0	1600	2300	8700	28800	1.080
	51222	160	38	113	160	1.1	1200	1800	15200	45000	2.570
	51322X	190	63	113	187	2.0	870	1200	26700	70500	7.870
	51422X	230	95	113	225	3.0	640	910	43500	124000	20.200
	51124	155	25	122	155	1.0	1500	2200	8900	30500	1.160
120	51224	170	39	123	170	1.1	1200	1700	15400	47000	2.860
	51324X	210	70	123	205	2.1	780	1100	31000	87000	10.900
	51424X	250	102	123	245	4.0	590	840	45580	134000	25.500
	51126	170	30	132	170	1.0	1300	1900	10400	35000	1.870
	51226X	190	45	133	187	1.5	1000	1500	20300	62000	4.190
130	51326X	225	75	134	220	2.1	720	1000	33000	96000	13.000
	51426X	270	110	134	265	4.0	540	770	55000	175000	32.000
	51128X	180	31	142	178	1.0	1300	1800	10700	37500	2.070
	51228X	200	46	143	197	1.5	980	1400	20500	65000	4.570
	51328X	240	80	144	235	2.1	670	960	35000	105000	15.900
140	51428X	280	112	144	275	4.0	520	740	54500	175000	34.500
	51130X	190	31	152	188	1.0	1200	1800	10900	40000	2.200
	51230X	215	50	153	212	1.5	900	1300	21300	65000	5.770
	51330X	250	80	154	245	2.1	660	940	36000	113000	16.700
	51430X	300	120	154	295	4.0	480	680	66500	221000	42.300
150	51132X	200	31	162	198	1.0	1200	1700	11200	42500	2.320
	51232X	225	51	163	222	1.5	870	1200	22300	72000	6.670
	51332X	270	87	164	265	3.0	600	850	41000	134000	21.500
	51432X	320	130	164	315	5.0	440	630	68000	241000	52.000
	51134X	215	34	172	213	1.1	1100	1600	13400	51000	3.320
160	51234X	240	55	173	237	1.5	800	1100	26100	83500	8.280
	51334X	280	87	174	275	3.0	580	830	42000	143000	22.500
	51434X	340	135	174	335	5.0	410	590	75500	273000	61.000