

Butées à billes à double effet à rondelles plates

d (mm)	Référence	Dimensions (mm)							Vitesses lim. (tr/mn)		Cap. de ch. (daN)		Masse (kg)	
		d1	d2	D	H1	B	a	remm	rlmm	Lubrification graisse huile	Dyn. C	Stat. Co		
65	52213	55	67	100	28.5	47	10	1.0	0.6	1900	2700	7500	18900	1.360
	52313	55	67	115	40.0	65	15	1.1	0.6	1500	2200	12700	26700	2.900
	52413	50	68	140	62.0	101	23	2.0	1.0	1100	1600	23100	49500	8.030
70	52214	55	72	105	28.5	47	10	1.0	1.0	1800	2600	7600	19900	1.480
	52314	55	72	125	44.0	72	16	1.1	1.0	1400	2000	14800	34000	3.900
	52414	55	73	150	65.5	107	24	2.0	1.0	1000	1500	25000	55500	9.710
75	52215	60	77	110	28.5	47	10	1.0	1.0	1800	2600	7750	20900	1.570
	52315	60	77	135	48.5	79	18	1.5	1.0	1300	1800	17000	36500	4.830
	52415	60	78	160	70.5	115	26	2.0	1.0	950	1400	25900	61500	11.800
80	52216	65	82	115	29.0	48	10	1.0	1.0	1700	2500	7850	21900	1.690
	52316	65	82	140	48.5	79	18	1.5	1.0	1200	1800	17600	42500	5.060
	52416	65	83	170	73.5	120	27	2.1	1.0	900	1300	27000	62000	14.000
85	52217	70	88	125	33.5	55	12	1.0	1.0	1600	2200	9550	26400	2.340
	52317	70	88	150	53.0	87	19	1.5	1.0	1100	1600	20000	49000	6.430
	52417X	65	88	180	78.5	128	29	2.1	1.1	840	1200	30500	75500	17.500
90	52218	75	93	135	38.0	62	14	1.1	1.0	1400	2000	11600	32500	3.220
	52318	75	93	155	53.5	88	19	1.5	1.0	1100	1600	19800	49000	6.600
	52418X	70	93	190	82.5	135	30	2.1	1.1	790	1100	32500	82500	19.600
100	52220	85	103	150	41.0	67	15	1.1	1.0	1300	1800	14600	41000	4.290
	52320	85	103	170	59.0	97	21	1.5	1.0	990	1400	23600	59500	8.900
	52420X	80	103	210	91.5	150	33	3.0	1.1	710	1000	34500	89500	26.600
110	52222	95	111	160	41.0	67	15	1.1	1.0	1200	1800	15200	45000	4.680
	52322X	95	111	190	67.0	110	24	2.0	1.0	870	1200	26700	70500	13.800
	52422X	90	113	230	101.5	166	37	3.0	1.1	640	910	43500	124000	34.900
120	52224	100	123	170	41.5	68	15	1.1	1.1	1200	1700	15400	47000	5.240
	52324X	100	123	210	75.0	123	27	2.1	1.1	780	1100	31000	87000	17.200
	52424X	95	123	250	108.5	177	40	4.0	1.5	590	840	45500	134000	44.200
130	52226X	110	133	190	49.0	80	18	1.5	1.1	1000	1500	20300	62000	7.720
	52326X	110	134	225	80.0	130	30	2.1	1.1	720	1000	33000	96000	22.100
	52426X	100	134	270	117.0	192	42	4.0	2.0	540	770	55000	175000	56.500
140	52228X	120	143	200	49.5	81	18	1.5	1.1	980	1400	20300	65000	8.930
	52328X	120	144	240	85.5	140	31	2.1	1.1	670	960	35000	105000	27.800
	52428X	110	144	280	120.0	196	44	4.0	2.0	520	740	54500	175000	60.600
150	52230X	130	153	215	54.5	89	20	1.5	1.1	900	1300	21300	65000	10.600
	52330X	130	154	250	85.5	140	31	2.1	1.1	660	940	36000	113000	29.200
	52430X	120	154	300	127.5	209	46	4.0	2.0	480	680	66500	221000	73.900
160	52232X	140	163	225	55.0	90	20	1.5	1.1	870	1200	22300	72000	12.200
	52332X	140	164	270	93.0	153	33	3.0	1.1	600	850	41000	134000	37.700
	52432X	130	164	320	138.0	226	50	5.0	2.0	440	630	68000	241000	90.300
170	52234X	150	173	240	59.0	97	21	1.5	1.1	800	1100	26100	83500	15.200
	52334X	150	174	280	93.0	153	33	3.0	1.1	580	830	42000	143000	39.800
	52434X	135	174	340	143.0	236	50	5.0	2.1	410	590	75500	273000	108.000