

Butées à billes à simple effet à une rondelle sphérique et une contreplaque

φ d (mm)	Référence		Dimensions (mm)										
	sans contreplaque	avec	D	B	D1 (max)	d1 (max)	R	A	rs (min)	d2	D2	H1	b
55	53211	53211 U	90	27.4	57	90	72	35.0	1.1	72	95	30	9.0
	53311	53311 U	105	39.3	57	105	80	30.0	1.1	80	110	42	11.5
	53411	53411 U	120	50.5	57	120	90	28.0	1.5	88	125	55	15.5
60	53212	53212 U	95	28.0	62	85	72	32.5	1.0	78	100	31	9.0
	53312	53312 U	110	38.3	62	110	90	41.0	1.1	85	115	42	11.5
	53412	53412 U	130	54.0	62	130	100	34.0	1.5	95	135	58	16.0
65	53213	53213 U	100	28.7	67	100	80	40.0	1.0	82	105	32	9.0
	53313	53313 U	115	39.4	67	115	90	38.5	1.1	90	120	43	12.5
	53413	53413 U	140	60.2	68	140	112	40.0	2.0	100	145	65	17.5
70	53214	53214 U	105	28.8	72	105	80	38.0	1.0	88	110	32	9.0
	53314	53314 U	125	44.2	72	125	100	43.0	1.1	98	130	48	13.0
	53414	53414 U	150	63.6	73	150	112	34.0	2.0	110	155	69	19.5
75	53215	53215 U	110	28.4	77	110	90	49.0	1.0	92	115	32	9.5
	53315	53315 U	135	48.1	77	135	100	37.0	1.5	105	140	52	15.0
	53415	53415 U	160	69.0	78	160	125	42.0	2.0	115	165	75	21.0
80	53216	53216 U	115	29.5	82	115	90	46.0	1.0	98	120	33	10.0
	53316	53316 U	140	47.6	82	140	112	50.0	1.5	110	145	52	15.0
	53416	53416 U	170	72.2	83	170	125	36.0	2.1	125	175	78	22.0
85	53217	53217 U	125	33.1	88	125	100	52.0	1.1	105	130	37	11.0
	53317	53317 U	150	53.1	88	150	112	43.0	1.5	115	155	58	17.5
	53417X	53417XU	180	77.0	88	177	140	47.0	2.1	130	185	83	23.0
90	53218	53218 U	135	38.5	93	135	100	45.0	1.1	110	140	42	13.5
	53318	53318 U	155	54.6	93	155	112	40.0	1.5	120	160	59	18.0
	53418X	53418XU	190	81.2	93	187	140	40.0	2.1	140	195	88	25.5
100	53220	53220 U	150	40.9	103	150	112	52.0	1.1	125	155	45	14.0
	53320	53320 U	170	59.2	103	170	125	46.0	1.5	135	175	64	18.0
	53420X	53420XU	210	90.0	103	205	160	50.0	3.0	155	220	98	27.0
110	53222	53222 U	160	40.2	113	160	125	65.0	1.1	135	165	45	14.0
	53322X	53322XU	190	67.2	113	187	140	51.0	2.0	150	195	72	20.5
	53422X	53422XU	230	99.7	113	225	180	59.0	3.0	170	240	109	29.0
120	53224	53224 U	170	40.8	123	170	125	61.0	1.1	145	175	46	15.0
	53324X	53324XU	210	74.1	123	205	160	63.0	2.1	165	220	80	22.0
	53424X	53424XU	250	107.3	123	245	200	70.0	4.0	185	260	118	32.0
130	53226X	53226XU	190	47.9	133	187	140	67.0	1.5	160	195	53	17.0
	53326X	53326XU	225	80.3	134	220	160	53.0	2.1	177	235	86	26.0
	53426X	53426XU	270	115.2	134	265	200	58.0	4.0	200	280	128	38.0

Butées à billes à simple effet à une rondelle sphérique et une contreplaque

φ d (mm)	Référence		Vitesse lim. (tr/mn) Lubrification		Cap. de ch. (daN) Dyn. Stat.		Masse (kg)	
	sans contreplaque	avec contreplaque	graisse	huile	C	Co	sans contreplaque	avec contreplaque
55	53211	53211 U	2100	3000	6950	15900	0.620	0.800
	53311	53311 U	1600	2300	12000	24600	1.400	1.700
	53411	53411 U	1300	1800	17800	36000	2.550	3.100
60	53212	53212 U	2000	2800	7350	17900	0.690	0.850
	53312	53312 U	1600	2300	12300	26700	1.450	1.750
	53412	53412 U	1200	1700	21300	43500	3.250	3.850
65	53213	53213 U	1900	2700	7500	18900	0.770	0.940
	53313	53313 U	1100	2200	12700	28700	1.600	1.950
	53413	53413 U	1100	1600	23100	49500	4.170	4.950
70	53214	53214 U	1800	2600	7600	19900	0.800	0.980
	53314	53314 U	1400	2000	14800	34000	2.150	2.550
	53414	53414 U	1000	1500	25000	55500	5.110	4.940
75	53215	53215 U	1800	2600	7750	20900	0.840	1.050
	53315	53315 U	1300	1900	17000	36500	2.700	3.250
	53415	53415 U	950	1400	26900	61500	6.250	7.600
80	53216	53216 U	1700	2500	7850	21900	0.930	1.160
	53316	53316 U	1200	1800	17600	42500	2.850	3.450
	53416	53416 U	900	1300	27000	62000	7.830	9.140
85	53217	53217 U	1600	2200	9550	26400	1.290	1.600
	53317	53317 U	1100	1600	20000	49000	3.650	4.450
	53417X	53417XU	840	1200	30500	75500	9.200	10.900
90	53218	53218 U	1400	2000	11600	32500	1.780	2.220
	53318	53318 U	1100	1600	19800	49000	3.890	4.700
	53418X	53418XU	790	1100	32500	82500	10.700	12.600
100	53220	53220 U	1300	1800	14600	41000	2.360	2.870
	53320	53320 U	990	1400	23600	59500	5.120	6.100
	53420X	53420XU	710	1000	34500	89500	14.500	17.200
110	53222	53222 U	1200	1800	15200	45000	2.530	3.000
	53322X	53322XU	870	1200	26700	70500	7.660	8.960
	53422X	53422XU	640	910	43500	124000	19.400	22.900
120	53224	53224 U	1200	1700	15400	47000	2.760	3.400
	53324X	53324XU	780	1100	31000	87000	10.400	12.400
	53424X	53424XU	590	840	45500	134000	24.600	29.200
130	53226X	53226XU	1000	1500	20300	62000	4.030	4.910
	53326X	53326XU	720	1000	33300	96000	12.600	15.200
	53426X	53426XU	540	770	55000	175000	30.400	36.700