

Butées à billes à double effet avec rondelles sphériques et contreplaques

φ d1 (mm)	Référence		Dimensions (mm)											
	sans contreplaque	avec	dmax	dø	d2	D	D1	H	H1	a	b	R	A	rle min
30	54207	54207 U	35	37	48	62	65	37.8	42	8	7.0	50	21.0	0.3
	54307	54307 U	35	37	52	68	72	47.2	52	10	7.5	56	21.0	0.3
	54208	54208 U	40	42	55	68	72	38.6	44	9	7.0	56	25.0	0.6
	54308	54308 U	40	42	60	78	82	54.0	59	12	8.5	64	23.5	0.6
	54408	54408 U	40	42	65	90	95	69.4	77	15	12.0	72	22.0	0.6
35	54209	54209 U	45	47	60	73	78	39.6	45	9	7.5	56	23.0	0.6
	54309	54309 U	45	47	65	85	90	56.2	62	12	10.0	64	21.0	0.6
	54409	54409 U	45	47	72	100	105	78.8	86	17	12.5	80	23.5	0.6
40	54210	54210 U	50	52	62	78	82	42.0	47	9	7.5	64	30.5	0.6
	54310	54310 U	50	52	72	95	100	64.6	70	14	11.0	72	23.0	0.6
	54410	54410 U	50	52	80	110	115	83.2	92	18	14.0	90	30.0	0.6
45	54211	54211 U	55	57	72	90	95	49.6	55	10	9.0	72	32.5	0.6
	54311	54311 U	55	57	80	105	110	72.6	78	15	11.5	80	25.5	0.6
	54411	54411 U	55	57	88	120	125	92.0	101	20	15.5	90	22.5	0.6
50	54212	54212 U	60	62	78	95	100	50.0	56	10	9.0	72	30.5	0.6
	54312	54312 U	60	62	85	110	115	70.6	78	15	11.5	90	36.5	0.6
	54412	54412 U	60	62	95	130	135	99.0	107	21	16.0	100	28.0	0.6
	54413	54413 U	65	68	100	140	145	109.4	119	23	17.5	112	34.0	1.0
55	54213	54213 U	65	67	82	100	105	50.4	57	10	9.0	80	38.5	0.6
	54313	54313 U	65	67	90	115	120	71.8	79	15	12.5	90	34.5	0.6
	54214	54214 U	70	72	88	105	110	50.6	57	10	9.0	80	36.5	1.0
	54314	54314 U	70	72	98	125	130	80.4	88	16	13.0	100	39.0	1.0
	54414	54414 U	70	73	110	150	155	114.2	125	24	19.5	112	28.5	1.0
60	54215	54215 U	75	77	92	110	115	49.6	57	10	9.5	90	47.5	1.0
	54315	54315 U	75	77	105	135	140	87.2	95	18	15.0	100	32.5	1.0
	54415	54415 U	75	78	115	160	165	123.0	135	26	21.0	125	36.5	1.0
65	54216	54216 U	80	82	98	115	120	51.0	58	10	10.0	90	45.0	1.0
	54316	54316 U	80	82	110	140	145	86.2	95	18	15.0	112	45.5	1.0
	54416	54416 U	80	83	125	170	175	128.4	140	27	22.0	125	30.5	1.0
	54417X	54417XU	85	88	130	180	185	138.0	150	29	23.0	140	40.5	1.1
70	54217	54217 U	85	88	105	125	130	59.2	67	12	11.0	100	49.5	1.0
	54317	54317 U	85	88	115	150	155	95.2	105	19	17.5	112	39.0	1.0
	54418X	54418XU	90	93	140	190	195	143.4	157	30	25.5	140	34.5	1.1
75	54218	54218 U	90	93	110	135	140	69.0	76	14	13.5	100	42.0	1.0
	54318	54318 U	90	93	120	155	160	97.2	106	19	18.0	112	36.5	1.0
80	54420X	54420XU	100	103	155	210	220	160.0	176	33	27.0	160	43.5	1.1

Butées à billes à double effet avec rondelles sphériques et contreplaques

φ di (mm)	Référence		Vitesses lim. (tr/mn)		Cap. de ch. (daN)		Masse (kg)	
	sans contreplaque	avec contreplaque	Lubrification graisse	huile	Dyn. C	Stat. Co	sans contreplaque	avec contreplaque
30	54207	54207 U	2700	3900	4700	9850	0.542	0.686
	54307	54307 U	2900	4200	3900	7800	0.431	0.550
	54208	54208 U	2400	3500	5550	10500	0.711	0.881
	54308	54308 U	2200	3100	6900	13500	1.100	1.330
	54408	54408 U	1700	2500	11200	20500	2.000	2.520
35	54209	54209 U	2600	3700	4750	10500	0.617	0.796
	54309	54309 U	2000	2900	8000	16300	1.280	1.630
	54409	54409 U	1600	2200	12900	24300	2.760	3.400
40	54210	54210 U	2400	3400	4850	11200	0.697	0.899
	54310	54310 U	1800	2600	9650	20200	1.920	2.370
	54410	54410 U	1400	2000	15700	31000	3.520	4.360
45	54211	54211 U	2100	3000	6950	15900	1.140	1.540
	54311	54311 U	1600	2300	12000	24600	2.650	3.220
	54411	54411 U	1300	1800	17800	36000	4.550	5.640
50	54212	54212 U	2000	2800	7350	17900	1.260	1.590
	54312	54312 U	1600	2300	12300	26700	2.760	3.390
	54412	54412 U	1200	1700	21300	43500	6.200	7.450
	54413	54413 U	1100	1600	23100	49500	8.010	9.670
55	54213	54213 U	1900	2700	7500	18900	1.350	1.720
	54313	54313 U	1500	2200	12700	28700	2.980	3.670
	54214	54214 U	1800	2600	7600	19900	1.480	1.860
	54314	54314 U	1400	2000	14800	34000	4.080	4.920
	54414	54414 U	1000	1500	25000	55500	9.500	11.500
60	54215	54215 U	1800	2600	7750	20900	1.530	1.960
	54315	54315 U	1300	1800	17000	36500	4.930	6.040
	54415	54415 U	950	1400	26900	61500	11.600	14.100
65	54216	54216 U	1700	2500	7850	21900	1.670	2.110
65	54316	54316 U	1200	1800	17600	42500	5.140	6.290
	54416	54416 U	900	1300	27000	62000	13.700	16.500
	54417X	54417XU	840	1200	30500	75500	17.300	20.700
70	54217	54217 U	1600	2200	9550	26400	2.340	2.930
	54317	54317 U	1100	1600	20000	49000	6.410	8.050
	54418X	54418XU	790	1100	32500	82500	19.100	23.000
75	54218	54218 U	1400	2000	11600	32500	3.250	4.120
	54318	54318 U	1100	1600	19800	49000	6.620	8.330
80	54420X	54420XU	710	1000	34500	89500	26.200	32.000