





2 lèvres**Pointage****Chanfreinage****Autocentrant****réf.****2426****SERIE COURTE**

Foret à pointer

Carbure Monobloc

tous matériaux

Ø A	LT	Lt	Ø B	Code Article
6	66	20	NOMINAL	D2426D0600
8	79	25		D2426D0800
10	89	25		D2426D1000
12	102	30		D2426D1200
16	115	35		D2426D1600

PERFORMANCE MATIERE

ACIER

< 1100 N/mm²< 1700 N/mm²< 2100 N/mm²

INOX MARTENSITIQUE FERRITIQUE

< 220 HB



INOX AUSTENITIQUE

< 220 HB



ACIER REFRACTAIRE

< 320 HB



ALLIAGE DE TITANE

< 1000 N/mm²

FONTE GRISE LAMELLAIRE

< 210 HB



FONTE GRISE

< 220 HB



ALUMINIUM ET SES ALLIAGES




CUIVRES ET SES ALLIAGES



MATERIAUX COMPOSITES



Attachement



Cylindrique

Caractéristiques

Coupe à droite
Hélice à droite : 25°
Nombre de lèvres : 2
Goujures : N
Affûtage : AF 12

Nature Outil

Carbure MK 15

Utilisation

USINAGE
VITESSE
CONVENTION-
NELLE

Lubrification

Arrosage extérieur

Normes

Normes Usine

Origines

Made in France

Profondeur Maxi

Tolérances

Ø A ► h7

Ø B ► h6

LT ► 0 / -1

Lt ► 0 / -1



VITESSES DE COUPE & AVANCE > PAGES 92 à 95

ISO 9001

