


Roulements de broche B70..-E

réglés, par paire ou par jeu, angle de contact $\alpha = 25^\circ$, tolérances réduites



	d mm	D mm	B mm
B7000-E-T-P4S	10	26	8
B7001-E-T-P4S	12	28	8
B7002-E-T-P4S	15	32	9
B7003-E-T-P4S	17	35	10
B7004-E-T-P4S	20	42	12
B7005-E-T-P4S	25	47	12
B7006-E-T-P4S	30	55	13
B7007-E-T-P4S	35	62	14
B7008-E-T-P4S	40	68	15
B7009-E-T-P4S	45	75	16
B7010-E-T-P4S	50	80	16
B7011-E-T-P4S	55	90	18
B7012-E-T-P4S	60	95	18
B7013-E-T-P4S	65	100	18
B7014-E-T-P4S	70	110	20
B7015-E-T-P4S	75	115	20
B7016-E-T-P4S	80	125	22
B7017-E-T-P4S	85	130	22
B7018-E-T-P4S	90	140	24
B7019-E-T-P4S	95	145	24
B7020-E-T-P4S	100	150	24
B7021-E-T-P4S	105	160	26
B7022-E-T-P4S	110	170	28
B7024-E-T-P4S	120	180	28
B7026-E-T-P4S	130	200	33
B7028-E-T-P4S	140	210	33
B7030-E-T-P4S	150	225	35
B7032-E-T-P4S	160	240	38
B7034-E-T-P4S	170	260	42
B7036-E-T-P4S	180	280	46
B7038-E-T-P4S	190	290	46
B7040-E-T-P4S	200	310	51
B7044-E-T-P4S	220	340	56
B7048-E-T-P4S	240	360	56