


Roulements de broche B719..-C

réglés, par paire ou par jeu, angle de contact $\alpha = 15^\circ$, tolérances réduites



	d mm	D mm	B mm
B71900-C-T-P4S	10	22	6
B71901-C-T-P4S	12	24	6
B71902-C-T-P4S	15	28	7
B71903-C-T-P4S	17	30	7
B71904-C-T-P4S	20	37	9
B71905-C-T-P4S	25	42	9
B71906-C-T-P4S	30	47	9
B71907-C-T-P4S	35	55	10
B71908-C-T-P4S	40	62	12
B71909-C-T-P4S	45	68	12
B71910-C-T-P4S	50	72	12
B71911-C-T-P4S	55	80	13
B71912-C-T-P4S	60	85	13
B71913-C-T-P4S	65	90	13
B71914-C-T-P4S	70	100	16
B71915-C-T-P4S	75	105	16
B71916-C-T-P4S	80	110	16
B71917-C-T-P4S	85	120	18
B71918-C-T-P4S	90	125	18
B71919-C-T-P4S	95	130	18
B71920-C-T-P4S	100	140	20
B71921-C-T-P4S	105	145	20
B71922-C-T-P4S	110	150	20
B71924-C-T-P4S	120	165	22
B71926-C-T-P4S	130	180	24
B71928-C-T-P4S	140	190	24
B71930-C-T-P4S	150	210	28
B71932-C-T-P4S	160	220	28
B71934-C-T-P4S	170	230	28
B71936-C-T-P4S	180	250	33
B71938-C-T-P4S	190	260	33
B71940-C-T-P4S	200	280	38
B71944-C-T-P4S	220	300	38
B71948-C-T-P4S	240	320	38