


Roulements de broche B719..-E

réglés, par paire ou par jeu, angle de contact $\alpha = 25^\circ$, tolérances réduites



	d mm	D mm	B mm
B71900-E-T-P4S	10	22	6
B71901-E-T-P4S	12	24	6
B71902-E-T-P4S	15	28	7
B71903-E-T-P4S	17	30	7
B71904-E-T-P4S	20	37	9
B71905-E-T-P4S	25	42	9
B71906-E-T-P4S	30	47	9
B71907-E-T-P4S	35	55	10
B71908-E-T-P4S	40	62	12
B71909-E-T-P4S	45	68	12
B71910-E-T-P4S	50	72	12
B71911-E-T-P4S	55	80	13
B71912-E-T-P4S	60	85	13
B71913-E-T-P4S	65	90	13
B71914-E-T-P4S	70	100	16
B71915-E-T-P4S	75	105	16
B71916-E-T-P4S	80	110	16
B71917-E-T-P4S	85	120	18
B71918-E-T-P4S	90	125	18
B71919-E-T-P4S	95	130	18
B71920-E-T-P4S	100	140	20
B71921-E-T-P4S	105	145	20
B71922-E-T-P4S	110	150	20
B71924-E-T-P4S	120	165	22
B71926-E-T-P4S	130	180	24
B71928-E-T-P4S	140	190	24
B71930-E-T-P4S	150	210	28
B71932-E-T-P4S	160	220	28
B71934-E-T-P4S	170	230	28
B71936-E-T-P4S	180	250	33
B71938-E-T-P4S	190	260	33
B71940-E-T-P4S	200	280	38
B71944-E-T-P4S	220	300	38
B71948-E-T-P4S	240	320	38