


Roulements de broche B72..-E

réglés, par paire ou par jeu, angle de contact $\alpha = 25^\circ$, tolérances réduites



	d mm	D mm	B mm
B7200-E-T-P4S	10	30	9
B7201-E-T-P4S	12	32	10
B7202-E-T-P4S	15	35	11
B7203-E-T-P4S	17	40	12
B7204-E-T-P4S	20	47	14
B7205-E-T-P4S	25	52	15
B7206-E-T-P4S	30	62	16
B7207-E-T-P4S	35	72	17
B7208-E-T-P4S	40	80	18
B7209-E-T-P4S	45	85	19
B7210-E-T-P4S	50	90	20
B7211-E-T-P4S	55	100	21
B7212-E-T-P4S	60	110	22
B7213-E-T-P4S	65	120	23
B7214-E-T-P4S	70	125	24
B7215-E-T-P4S	75	130	25
B7216-E-T-P4S	80	140	26
B7217-E-T-P4S	85	150	28
B7218-E-T-P4S	90	160	30
B7219-E-T-P4S	95	170	32
B7220-E-T-P4S	100	180	34
B7221-E-T-P4S	105	190	36
B7222-E-T-P4S	110	200	38
B7224-E-T-P4S	120	215	40
B7226-E-T-P4S	130	230	40
B7228-E-T-P4S	140	250	42
B7230-E-T-P4S	150	270	45
B7232-E-T-P4S	160	290	48
B7234-E-T-P4S	170	310	52
B7236-E-T-P4S	180	320	52
B7238-E-T-P4S	190	340	55
B7240-E-T-P4S	200	360	58
B7244-E-T-P4S	220	400	65