


Roulements à rouleaux cyl. NNU49..-S-K-M-SP

dimensions principales selon DIN 5412-4, palier libre, à 2 rangées, avec alésage conique, cône 1:12, dissociable, avec cage, jeu radial réduit, tolérances réduites



	d mm	D mm	B mm
NNU4920-S-K-M-SP	100	140	40
NNU4921-S-K-M-SP	105	145	40
NNU4922-S-K-M-SP	110	150	40
NNU4924-S-K-M-SP	120	165	45
NNU4926-S-K-M-SP	130	180	50
NNU4928-S-K-M-SP	140	190	50
NNU4930-S-K-M-SP	150	210	60
NNU4932-S-K-M-SP	160	220	60
NNU4934-S-K-M-SP	170	230	60
NNU4936-S-K-M-SP	180	250	69
NNU4938-S-K-M-SP	190	260	69
NNU4940-S-K-M-SP	200	280	80
NNU4944-S-K-M-SP	220	300	80
NNU4948-S-K-M-SP	240	320	80
NNU4952-S-K-M-SP	260	360	100
NNU4956-S-K-M-SP	280	380	100
NNU4960-S-K-M-SP	300	420	118
NNU4964-S-K-M-SP	320	440	118
NNU4968-S-K-M-SP	340	460	118
NNU4972-S-K-M-SP	360	480	118
	d mm	D mm	B mm
NNU4976-S-K-M-SP	380	520	140
NNU4980-S-K-M-SP	400	540	140
NNU4984-S-K-M-SP	420	560	140
NNU4988-S-K-M-SP	440	600	160
NNU4992-S-K-M-SP	460	620	160
NNU4996-S-K-M-SP	480	650	170
NNU49/500-S-K-M-SP	500	670	170