


Manchons de serrage H2

dimensions principales selon DIN 5415, cône 1:12



	d _{1H} mm	D _m mm	l mm
H203	14	28	21
H204	17	32	24
H205X012	19,05	38	26
H205	20	38	26
H205X013	20,638	38	26
H206X014	22,225	45	27
H206X015	23,812	45	27
H206	25	45	27
H206X100	25,4	45	27
H207X102	28,575	52	29
H207	30	52	29
H207X103	30,162	52	29
H208X104	31,75	58	31
H208X105	33,338	58	31
H208X106	34,925	58	31
H208	35	58	31
H209X107	36,513	65	33
H209X108	38,1	65	33
H209	40	65	33
H210X111	41,275	70	35
	d _{1H} mm	D _m mm	l mm
H210X110	41,275	70	35
H210X112	44,45	70	35
H210	45	70	35
H211X114	47,625	75	37
H211X115	49,213	75	37
H211	50	75	37
H211X200	50,8	75	37
H212X202	53,975	80	38
H212	55	80	38
H213X203	55,563	85	40
H213X204	57,15	85	40
H214	60	92	41
H213	60	85	40
H213X206	60,325	85	40

H215X207	61,913	98	43
H215X208	63,5	98	43
H215	65	98	43
H215X210	66,675	98	43
H216X211	68,263	105	46
H216X212	69,85	105	46
	d_{1H} mm	D_m mm	l mm
H216	70	105	46
H216X214	73,025	105	46
H217X215	74,612	110	50
H217	75	110	50
H217X300	76,2	110	50
H218X302	79,375	120	52
H218	80	120	52
H218X303	80,962	120	52
H218X304	82,55	120	52
H219	85	125	55
H219X306	85,725	125	55
H220X307	87,313	130	58
H220X308	88,9	130	58
H220	90	130	58
H220X310	92,075	130	58
H220X311	93,663	130	58
H221	95	140	60
H222X312	95,25	145	63
H222X314	98,425	145	63
H222	100	145	63
	d_{1H} mm	D_m mm	l mm
H222X315	100,012	145	63
H222X400	101,6	145	63