

Terostat-IX

Permanently Plastic, Unformed Sealant
for Application in Industry and Craft

Basis: Synthetic Rubber

Status: 2002-05-23

Product Information
Produktinformation
Information produit
Información del producto

Henkel

Teroson

Product Description

Terostat-IX is a solvent free, permanently plastic, pressure sensitive sealant based on synthetic rubber. It serves as a good corrosion protection and can be painted with conventional paints based on oil and synthetic resins. The material exhibits very good water and aging resistance. Due to its tackiness the sealant adheres to all clean and dry surfaces and shows excellent compatibility with a variety of substrates.

Application Areas

Terostat-IX is used as a shapeless kneading mass in the automotive, wagon and caravan industry, sheet fabricating industry and construction industry, for example for closing holes, cable openings and in the field of sanitary installations.

Technical Data

Colour:	light grey
Odour:	slight – of mineral oil
Consistency:	soft plastic, adhesive, kneadable
Density:	1.7 g/cm ³
Solids:	100 %
Penetration:	ca. 75 ¹ / ₁₀ mm
(cone 150 g, 6 s, 23°C)	
Tackiness:	low
Paintability:	can be painted
In service temperature range:	-30°C–80°C
Temperature resistance:	160°C
Short exposure (up to 1 hr.):	160°C

Preliminary remark

Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

Terostat-IX is applied by hand by tearing off desired quantities from the mass. This portion is pressed into place in the desired form by hand, a smoothing wood, spatula or similar. Due to its tackiness Terostat-IX provides an effective seal.

Storage

Frost-sensitive	no
Recommended storage temp.	15°C to 25°C
Shelf-life	12 months in original packaging

Packaging

Blisterpack *	200 g	Art.-No. 128.95 R (D/GB/F/NL)
Tin	1 kg	Art.-No. 157.86 J (D/GB/F/NL)
Pail	16 kg	Art.-No. 171.70 N (D/GB/F/NL)
Tin	1 kg	Art.-Nr. 181.27 N (S/SF/DK/N)

* as Kneading mass

**Hazard Indications/
Safety Recommendations/
Transport Regulations**

see Safety Data Sheet

Important

The above data, particularly the recommendations for application and use of our products are based on our knowledge and experience. Due to different materials and conditions of application which are beyond our knowledge and control we recommend strongly to carry out sufficient tests in order to ensure that our products are suitable for the intended processes and applications. Except for wilful acts any liability based on such recommendations or any oral advice is hereby expressly excluded.

This Technical Data Sheet supersedes all previous editions.

Germany:

Henkel KGaA
D-40191 Düsseldorf
Telefon (06221) 704-0
Telefax (06221) 704-698

UK:

Henkel Loctite Adhesives Ltd.
Watchmead
Welwyn Garden City
Hertfordshire AL 7 1 JB
Telephone (01707) 35 88 00
Telefax (01707) 35 89 00